

DRYTAC®



JETMOUNTER™

ROLLER LAMINATORS

JM63 PRO

The JM63 Pro is a full-feature, versatile, wide-format roller laminator with roll-to-roll capability at an excellent price. The addition of the heated top roller allows it to be used with Heatset® and thermal overlaminates as well as pressure sensitive overlaminates and adhesives.

Features:

- Heated top roller up to 120°C (248°F)
- 1600 mm (63") laminating width
- Large 139.7 mm (5.5") diameter non-stick silicone rollers
- Auto and foot pedal operation modes
- Speed control up to 3.65 m (12 ft) per minute
- Maximum 50 mm (2") nip opening
- Nip pressure indicator
- Fold away front table
- Heavy-duty lockable casters
- Two top-mounted emergency stops
- "Hold flat" paper in-feed guide
- Self-checking photo cells for finger protection
- Top and bottom supply shafts with brake tension control
- Top and bottom wind-up shafts with adjustable clutch speed
- Extra rear wind-up shaft for rewinding roll-to-roll
- Single mechanical height/pressure adjustment
(No compressor needed)



JM63 PRO



JM63 PRO SPECIFICATIONS

Max Laminating Width	1600 mm (63")
Max Nip Opening	50.8 mm (2")
Uncrated Weight	440 kg (970 lbs)
Width	2108 mm (83")
Depth	737 mm (29") w/o table up 813 mm (32") w/ table up
Height	1244 mm (49")
Roller Diameter	139.7 mm (5.5")
Speed Range	0 - 3.65 mpm (0 - 12 fpm)
Power	230V 50/60Hz, 13A Single Phase

JM55 & JM63 FUZION

The JM55 and JM63 Fuzion have many of the features of the JM63 Pro, but in a two-part construction and at a lower price point. Excellent for laminating vehicle wraps, creating window decals and mounting graphics to substrates, the Fuzion models are ideal for shops wanting to add roll-to-roll capability at a lower price tag.

JM55 & JM63 FUZION SPECIFICATIONS

	JM55 FUZION	JM63 FUZION
Max Laminating Width	1397 mm (55")	1600 mm (63")
Max Nip Opening	25 mm (1")	25 mm (1")
Uncrated Weight	260 kg (573 lbs)	285 kg (628 lbs)
Width	1854 mm (73")	2108 mm (83")
Depth	610 mm (24")	610 mm (24")
Height	1220 mm (48")	1220 mm (48")
Heat Assist Roller	Yes (43°C/110°F)	Yes (43°C/110°F)
Roller Diameter	139.7 mm (5.5")	139.7 mm (5.5")
Speed Range	0.6 - 3 mpm (2 - 10 fpm)	0.6 - 3 mpm (2 - 10 fpm)
Power	230V 50/60Hz, 13A Single Phase	230V 50/60Hz, 13A Single Phase



JM55 FUZION



The design of our JetMounter™ roller laminators is the culmination of three decades of experience in the mounting and laminating business. Equipped with the performance features our customers demand, JetMounter™ roller laminators are unmatched for value.



JM EXTREME



JM EXTREME

The JM Extreme is designed with the most superior quality and durable construction of all the JetMounter™ roller laminators. German steel and European engineering make the JM Extreme the most comprehensive roller laminator on the market and ideal for any high volume shop. Features include comfortable, precise material control adjustments, a take-up roller for roll-to-roll capability, and top and bottom heated rollers. The JM Extreme also has two global safety systems with an emergency stop.

Features:

- Heated top and bottom roller up to 130 °C (266 °F)
- 1650 mm (65") laminating width
- Robust design with leveling legs for installation in uneven environments and wheels for increased mobility
- Precise tolerances and material controls
- Easy-to-use control panel to manage variable temperature, speed and roller nip
- Anti-stick silicone rollers
- Extra wind and unwind shafts for roll-to-roll capability and flexibility (2 wind, 2 unwind and 1 extra)
- Rear roll traction system to control material tension
- Ergonomic front feeder table for ease of loading
- Easy adjustment of film using brake tension
- Photo-cell safety protection
- Pedal control for hands-free operation
- Two global safety systems with emergency stop

JM EXTREME SPECIFICATIONS

Max Laminating Width	1650 mm (65")
Max Nip Opening	40 mm (1.5")
Uncrated Weight	850 kg (1874 lbs)
Width	2220 mm (87")
Depth	785 mm (31")
Height	1320 mm (52")
Roller Diameter	127 mm (5")
Maximum Speed	4 mpm (12 fpm) or 12 mpm (39 fpm) with optional upgrade
Heated Roller (top and bottom)	Yes (130 °C/266 °F)
Power	230-240V 50Hz, 38A Single Phase

JM44 & JM55 SHA

The JM44 and JM55 SHA boast an all-steel construction, variable speed electric drive, silicone rollers, forward and reverse, foot pedal, photo-cell safety protection, single height adjuster to set even pressure, LCD pressure gauge display for greater control, and a front-mounted media unwind tray with supply shaft for feeding media or other material.



JM44 SHA



JM44 & JM55 SHA SPECIFICATIONS

	JM44 SHA	JM55 SHA
Max Laminating Width	1130 mm (44.5")	1420 mm (56")
Max Nip Opening	25 mm (1")	25 mm (1")
Uncrated Weight	122 kg (269 lbs)	153 kg (337 lbs)
Width	1539 mm (61")	1800 mm (71")
Depth	480 mm (19")	480 mm (19")
Height	480 mm (19") w/o stand 1237 mm (48.7") w/ stand	
Roller Diameter	102 mm (4")	130 mm (5")
Speed Range	0.6 - 3 mpm (2 - 10 fpm)	0.6 - 3 mpm (2 - 10 fpm)
Front Media Unwind Tray	Yes	Yes
Power	230V 50/60Hz, 13A Single Phase	230V 50/60Hz, 13A Single Phase

JM18, JM26 & JM34

These smaller JetMounter™ models are motorised table-top laminators operated by a foot switch, leaving both hands free to handle the work being processed. The JM18, JM26 and JM34 are designed for mounting and laminating inkjet output, but are equally capable of handling photographic or any printed media. All models include a supply shaft and photo cells for finger protection.

Note: There are no rewind shafts on these models.



JM18, JM26 & JM34 SPECIFICATIONS

	JM18	JM26	JM34
Max Laminating Width	460 mm (18.25")	667 mm (26.25")	870 mm (34.25")
Max Board Thickness	25 mm (1")	25 mm (1")	25 mm (1")
Weight	23 kg (51 lbs)	24 kg (53 lbs)	32 kg (70.5 lbs)
Width	650 mm (25.5")	845 mm (33.25")	1050 mm (41")
Depth	300 mm (11.75")	310 mm (12")	300 mm (11.8")
Height	330 mm (13")	310 mm (12")	340 mm (13.38")
Speed Range	0.76 - 5.5 mpm (2.5 - 18 fpm)	0.76 - 5.5 mpm (2.5 - 18 fpm)	0.76 - 5.5 mpm (2.5 - 18 fpm)
Power	110V 50/60Hz	110V 50/60Hz	110V 50/60Hz

ML13 & ML25

These table-top manual laminators are inexpensive options for small photo studios or copy shops that want a quick solution to mount or laminate small pieces. Simple, durable construction make these models easy to use. They also fold up for easy storage and transport.



ML13 & ML25 SPECIFICATIONS

	ML13	ML25
Max Laminating Width	343 mm (13.5")	648 mm (25.5")
Max Nip Opening	25 mm (1")	25 mm (1")
Weight	11 kg (24 lbs)	14 kg (31 lbs)
Width	390 mm (15.375")	695 mm (27.375")
Depth	622 mm (24.5")	622 mm (24.5")
Height	260 mm (10.25")	260 mm (10.25")
Roller Diameter	63 mm (2.5")	63 mm (2.5")

Contact your local distributor:

DRYTAC®

+44 (0) 117-958-6500
www.drytac.com