

# EasyGUARD

## Highlights

- > Universal laminating foil for short-term advertising applications
- > It gives attractive finish and protects against UV rays and abrasions
- > meets REACH regulations

## Technical Data Sheet

<b>Materiał</b>	Transparentna, błyszcząca / matowa samoprzylepna kalandrowana folia PCW, przeznaczona do zabezpieczania wielkoformatowych wydruków
<b>Type of coating (DIN 60001)</b>	Powlekany PE papier, silikonowy
<b>Thickness</b>	80±10 mic
<b>Backing paper thickness</b>	100±10 gsm
<b>Adhesive</b>	Polyakrylan rozpuszczalnikowy, trwały
<b>Adhesion power</b>	8 N/25 mm (FINAT TM 1, po 24h, stal nierdzewna)
<b>Tensile strength (ASTM D882-02; 200mm/Min)</b>	along min 23Mpa across min 20Mpa
<b>Recommended lamination temperature</b>	+ 20°C - + 35°C
<b>Sutable temperature</b>	- 20°C do + 65°C
<b>External durability</b>	12 months*
<b>Recommended vinyl</b>	EasyPRINT Vinyl / EasyPRINT Vinyl Grey
<b>Roll lenghts / product codes</b>	106 cm x 50 m (Art-Nr. L-EGUARDGLOSSYR106-50) 137 cm x 50 m (Art-Nr. L-EGUARDGLOSSYR137-50) 160 cm x 50 m (Art-Nr. L-EGUARDGLOSSYR160-50)

\*Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.





