

SOLVENT SO600-- SOLVENT BACKLIT 200 MATTE

Translucent polyester coated backlit film is designed for top quality graphic arts application in light boxes with high contrast. The semi-matte coating reduces glare, provides high quality image density. The printouts are characterized by high ink density, vivid colors, and outstanding image resolution with/without light. Compatible to all the popular solvent and UV curable inkjet printers. Work with all the popular solvent, Latex and UV curable inkjet printers. It is also easy to install because of very good rigidity and flatness of 8 mil base polyester film.

APPLICATION

Light box graphic
 Backlit Trade show display
 Department store display
 luminous advertising
 Bus shelter & Metro illuminated signage

LATEX PRINTING MEDIA (NEW PRINTER APPLICATION)


SPECIFICATION

Caliper	205 micron (8.2 mil)
weight	275g
Base material	Polyester film
Surface	Semi Matte
Width	36", 42", 50", 60"
Length	30m (100 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility



Printer Compatil

Most Solvent & Eco Solvent Printing system: LATEX & HP, Epson, Roland, Mimaki, Mutoh, Seiko, Oce

TECHNICAL DATA

Caliper	205micron	ASTM D645
Gloss	5/8	ASTM D2457
L.a.b	85/ 1 / -7	ANSI T D50/2 ^o /Abs/No

GUIDELINES

- Printing Tip** Dry time will vary depending on ink type. It is necessary to dry up and not to overlap the printed material.
- Lamination:** Lamination is optional. In order to protect the image from physical damage, overlaminates is recommended.
- Storage:** It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~30°C (50°~86°F), Humidity 35~65% RH
- Shelf Life:** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.