

## PRODUCT DATA SHEET



### Avery® MPI™ 2800 Series

issued: 6/2012

#### Introduction

Avery Multi Purpose Inkjet 2800 series films are gloss white, self-adhesive polymeric calendered vinyls, offering a choice between permanent and removable adhesives, also available with grey barrier coat for overposting needs.

Avery MPI 2800 series is highly recommended for a wide range of applications on flat and slightly curved substrates, with great price/performance ratio for short or medium term applications.

#### Description

Film	: MPI 2800 series	80 micron gloss white polymeric calendered vinyl
Adhesive	: MPI 2800 MPI 2801 MPI 2802 MPI 2803	Permanent, clear, acrylic based Removable, clear, acrylic based Removable, grey, acrylic based Permanent, grey, acrylic based
Backing paper	: MPI 2800 series	PE coated kraft paper, 126 g/m2

#### Conversion

MPI 2800 series films are multi-purpose vinyls, suitable for a variety of wide format inkjet printers using hard solvent, eco/mild solvent, UV-curing or latex inks.

To enhance colour and to protect images against UV radiation and abrasion, it is recommended to protect Avery MPI 2800 series films using an overlamine or varnish.

For recommended combinations of DOL films and media, please refer to "Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media".

#### Uses

- Large fleet graphics on flat or slightly curved surfaces
- Architectural interior & exterior signs
- Overposting existing graphic applications
- Temporary promotional and point of sales advertising

#### Features

- Excellent price/performance ratio for outdoor promotional graphics
- Great print results and handling on selected printers
- High gloss or matt finishes\*
- High opacity for overposting needs
- Outdoor durability, up to 5 years unprinted
- ICS Performance Guarantee



www.averygraphics.com

#### Graphics Division

Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude – The Netherlands  
Tel +31 71 3421500 – Fax +31 71 3421538

## PRODUCT CHARACTERISTICS

## Avery® MPI™ 2800 Series

### Physical properties

Features		Test method <sup>1</sup>	Results
Caliper, facefilm		ISO 534	80 micron
Caliper, facefilm + adhesive		ISO 534	100 micron
Dimensional stability		DIN 30646	0.3 mm max
Adhesion			
<b>MPI 2800/2803</b>	initial	FINAT FTM-1, stainless steel	350 N/m
	ultimate	FINAT FTM-1, stainless steel	550N/m
<b>MPI 2801/2802</b>	initial	FINAT FTM-1, stainless steel	200 N/m
	ultimate	FINAT FTM-1, stainless steel	250 N/m
Flammability			Self-extinguishing
Shelf life		Stored at 22° C/50-55 % RH	2 years
Durability, unprinted		Vertical exposure	5 years

### Temperature range

Features	Results
Minimum application temperature:	≥ + 10 °C
Service temperature:	- 40 °C to + 100 °C

**NOTE:** Materials have to be properly dried before further processing, for example laminating, varnishing or application. The residual solvents could change the products' specific features.

### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall be controlling.

### Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

#### 1) Test methods

More information about our test methods can be found on our website.

#### 2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

