Details

- · Premium white PP based
- · Removable , Repositionable
- \cdot Excellent block out to express vivid image
- · Available on various smooth surfaces such as PMMA
- · Minimize residue left behind on the surface

Specifications

Length (m)	30	Width (inch)	54"
Weight (g/m²)	265	Coating	Resin
Caliper (um)	260	Base Material	PP
Inner Core (inch)	3	Printer	
Surface	Semi - Matte	Peel Strength (180° gf/25mm)	20 ≥ (20 min) 50 ≥ (24 hr)

KEY FEATURES

- Premium white PP based
- Removable, Repositionable
- Excellent block out
- Various range of application
- Minimize residue left behind on the surface

Application

· Retail window advertisements, indoor window advertisements, Architectural window decorations

General Information

- \cdot Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- · Lamination : Optional
- · Storage : Recommended to strore in closed original packing in a cool 10 $^{\sim}$ 30 $^{\circ}$ C (50 $^{\sim}$ 77 $^{\circ}$ F) and dry environment. (Humidity 35 $^{\sim}$ 65% RH)
- $\boldsymbol{\cdot}$ Shelf Life : One year, stored in original packing at recommended temperature
- * Installation tip

Not recommended for outdoor usage

Clean the mounting object before applying this film

Wet mounting application

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.



 Head office (Korea)
 Europe Branch (Belgium)

 Natura Media Inc.
 Natura Europe S.A

 Tel: +82-(0)2-3788-0331
 Tel: +32-65-321-562

 Fax: +82-(0)2-3788-0326
 Fax: +32-65-470-393

 sales@naturamedia.co.kr
 jh.hong@naturamedia.co.kr

Natura Meida USA

Natura Media USA Inc.
Tel: +1-470-359-2111
Fax: +1-470-359-2199
sales@naturamedia.us