



UV Backlit 180 (TEU300)

GENERAL INFORMATION

≫ Product Description

 ${\sf UV}\ {\sf backlit}\ {\sf is}\ {\sf a}\ {\sf single}\ {\sf side}\ {\sf coated},\ {\sf antistatically}\ {\sf -treated}\ {\sf polyester}\ {\sf backlit}\ {\sf film}\ {\sf for}\ {\sf UV}\ {\sf -curable}\ {\sf ink}$

Direct Image on the front (Satin) surface yields images with maximum

ink density, vivid color and high image resolution for either reflective or backlit viewing

in both indoor and outdoor applications.

The special satin coating is adopted to the gloss level of UV curable ink to reduce finish diffrence.

The fixation of the UV ink to the surface is very strong and UV lamb can be run on reduced

performance. (Low) to avoide high tempertures and a possible cracking of the ink.

≫ Special Feature

Premium flatness PET Based

Premium White color surface

High quality color reproduction with and without light

Stability of production and printing Anti-Scratch (Hardness surface)

≫ Physical Feature

180 Micron Caliper with special base material / Glossy finished surface

≫ Areas of Application

Light Box Advertisement But & subway Advertisement Department store display Photo quality printing

≫ Inks of Application



≫ Printer Applications

Colorspan , Zünd UVjet , UV-curable Scitex , StellarJet, Oce UV Inkjet Printer

ORDER INFORMATION

➤ Order Code No.
TEU300-- : UV BACKLIT 180

>> MOQ 49 rolls per width (1 pallet)

Head Office 12F ShinhanDM Bldg., Mapo Street 25, Mapo-gu, Seoul, Korea 121-708

Tel: +82-(0)2-3788-0365, Fax: +82-(0)2-3788-0326, E-mail:Sales@naturamedia.co.kr

Natura Europe S.A Rue Descartes 2,B-7000 MONS, BELGIUM

Tel: +32-65-225-509, Fax: +32-65-554-174, E-mail: jh.hong@naturamedia.co.kr

≫ Natura JAPAN コーワ化成株式会社,東京都千代田区神田須田町2-19-34 (Web: www.kowa-ksi.co.jp)

Tel. +81-3-5296-9701(代表), Fax. +81-3-5296-9700, E-mail: yuichi.takano@kowa-ksi.co.jp

TECHNICAL INFORMATION

Physical Properties

	Valuation	Test Standardization
Caliper	180Micron	ASTM D645
L.a.b	85 / -1 / 0	ANSI T(D50/2º/Abs/No)
Yellowness	40	ASTM D1925
Glossiness	5 / 15	ASTM D2457

STOCKING INFORMATION

≫ Storage

Products are recommended to avoid direct sunlight and keep at a chilly place.

Resual cloth puts it in a vinyl bag like finished goods packing,

and I keep it after box packing after use.